

Panel PC

MUSE FS/FS/D/I

12.1"~22" Rugged Multimedia Panel PC



Specifications

- **CPU**
 - ◆ MUSE FS : Intel® Atom™ processor D425, 512K Cache, 1.80 GHz (single core)
 - ◆ MUSE FD : Intel® Atom™ processor D525, 1M Cache, 1.80 GHz (dual core)
 - ◆ MUSE D: Intel Celeron 2.0 GHz up to Core 2 Duo 2.8 GHz
 - ◆ MUSE I : Intel Socket 1155 for Intel Core™ i7 /Core™ i5 /Core™ i3
- **System Chipset**
 - ◆ MUSE FS/FD: Intel Pineview-D & ICH8M
 - ◆ MUSE D: Intel 945 G/GC & ICH7
 - ◆ MUSE I : Intel H67
- **System Memory**
 - ◆ MUSE FS/FD: 1 x 200 pin SO DIMM DDR2 up to 2GB
 - ◆ MUSE D: 2 x 240 pin DDR2 up to 4GB
 - ◆ MUSE I : 2 x 240 pin DDR3 up to 8GB
- **System Display**
 - ◆ MUSE 120: 12.1" TFT LCD, 800 x 600
 - ◆ MUSE 150: 15" TFT LCD, 1024 x 768
 - ◆ MUSE 170: 17" TFT LCD, 1280 x 1024
 - ◆ MUSE 190: 19" TFT LCD, 1280 x 1024
 - ◆ MUSE 200: 20" TFT LCD, 1600 x 1200
 - ◆ MUSE 220: 22" TFT LCD, 1680 x 1050
 - ◆ Supports Dynamic Video Memory Technology(DVMT)
- **Standard I/O**
 - ◆ Serial ports x4 (COM1,2,4 with +5V/12V power output on pin 9); COM 3 is internal type reserved for touchscreen)
 - ◆ Parallel port x 1 (SPP/EPP/ECP)
 - ◆ VGA interface x 1
 - ◆ USB interface MUSE F/D x 4 / MUSE I x 8
 - ◆ E-SATA interface x 2 (MUSE I only)
 - ◆ HDMI interface x 1 (MUSE I only)
- **Audio**
 - ◆ Speaker x 2
 - ◆ Speaker-out, Line-in & MIC-in
- **Ethernet**
 - ◆ 10/100/1000 Base-T with RJ-45
 - ◆ Supports Wake-on-LAN
- **Power Supply**
 - ◆ 120W, 100~240V/ 1.2A @50~60Hz

Peripheral & Storage Devices

- **Touchscreen**
 - ◆ Resistive type or capacitive type
- **Drive Bay**
 - ◆ 2.5" HDD SATA interface
- **Optional Device**
 - ◆ Magnetic card reader (swipe type)
 - ◆ Wireless LAN

Mechanical / Environmental

- **Construction**
 - ◆ Enclosure: heavy-duty steel
 - ◆ Front bezel: die casting aluminum alloy



Desktop stand



Yoke mount desktop



Wall mount



Panel mount

*Specifications are subject to change without prior notice