

# OFP215

21.5" Full HD Digital Signage System with Intel® Atom™ Processor N330 1.6 GHz



## Features



- 21.5" 16:9 TFT LCD - Full HD 1920 x 1080p
- Intel® Atom™ processor N330 1.6 GHz with 533 MHz MT/s
- With Intel® Gen 3.5 high performance integrated graphics controller
- S-video out
- VESA FPMPI compliant flat panel mounting
- Built-in SAW touch (optional)

## Specifications

|                    |   |                                     |
|--------------------|---|-------------------------------------|
| LCD Panel          | Size  | 21.5"                               |
|                    | Contrast  | 1000 : 1                            |
|                    | Pixel Pitch   | 248 x 248 (um)                      |
|                    | Viewing Angle (H/V)                                       | 160° x 170°                         |
|                    | Response Time   | 5ms                                 |
|                    | Color   | 16.7M                               |
|                    | Brightness (cd/m <sup>2</sup> )                           | 300                                 |
| Board              | CPU   | Intel® Atom™ processor N330 1.6 GHz |
|                    | Onboard Graphics  | Intel® 945GC                        |
|                    | Front Side Bus  | 533 MHz                             |
|                    | Memory  | 1 x 240-pin DIMM max up to 2GB      |
|                    | HDD   | 1 x 2.5" HDD                        |
| I/O                | 4 x USB 2.0   |                                     |
|                    | 1 x parallel port   |                                     |
|                    | 1 x RS-232  |                                     |
| Ethernet           | 1 x 10/100/1000Mbps Ethernet                              |                                     |
| Expansion Slot     | N/A   |                                     |
| Audio              | Line-in/Line-out/Mic                                      |                                     |
| Touchscreen        | Surface acoustic wave (SAW) type (optional)               |                                     |
| Power Supply       | 19V <sub>dc</sub> , with AC-DC adapter                    |                                     |
| Dimensions         | 319mm (12.5") (W) x 90.8mm (3.6") (D) x 527mm (20.7") (H) |                                     |
| Packing dimensions | 635mm (25") (W) x 420mm (16.53") (D) x 198mm (7.8") (H)   |                                     |
| Weight(net/gross)  | 9.8 kg ( 21.6 lb)/11.2 kg (24.6 lb)                       |                                     |
| Environmental      | 0 - +40 °C, operation, 10% - 95% relative humidity        |                                     |

## Ordering Information

|          |  |
|----------|--|
| OFP215   | 21.5" digital signage platform with Intel® Atom™ processor N330 1.6 GHz, 1920 x 1080P full HD resolution                   |
| OFP215-S | 21.5" digital signage platform with Intel® Atom™ processor N330 1.6 GHz, 1920 x 1080P full HD resolution, SAW touch screen |

## Dimensions

