PANEL1175-831

17"TFT Slim Intel[®] Core™2 Duo Industrial Panel Computer



1. IEEE 1394a	4. PS/2 K/B+M/S	7. USB 2.0 x 4
2. COM 1/2 (RS-232)	5. VGA	8. Audio (Mic-in/Line-out)
3. Power switch	6. Ethernet x 2	9. COM 1 (RS-232/422/485)

Features

- 17" SXGA TFT LCD display
- ► Superior Intel[®] Core[™]2 Duo processor
- ► Intel[®] 945GME+ICH7M chipset
- Ultra slim design: thickness 84mm
- Built-in two speakers
- Supports WLAN antenna (optional)
- Supports Windows® Vista Home
- Panel/Rack/VESA mounting ways



Side view

Introduction

The PANEL1175-831 is a multi-media panel PC designed for kiosk application. It is equipped with 17" TFT LCD display and advanced Intel[®] Core^{TM2} Duo processor. To answer the demand of multimedia application, the PANEL1175-831 supports Windows[®] Vista operating system and adopts built-in speakers, two Gigabit LAN, IEEE 1394a and WLAN module for wireless connectivity. In addition, this panel computer has a slim and fashionable mechanism design with thickness of 84mm only to be fit in with limited space. Thus, the PANEL1175-831 is best suitable for kiosk, public information system and more.

Powerful computing: Intel[®] Core[™]2 Duo processor The PANEL1175-831 features Intel[®] Core[™]2 Duo processor and Intel[®] 945GME chipset which deliver high computing capability. The Mobile CPU offers reliable and stable performance for rugged environment.

Specifications

Front Bezel	Aluminum with IP65/NEMA 4 rugged protection and brightness control bottons	
	Display Type	17" SXGA TFT
	Brightness (cd/m ²)	260 nits
	Resolution	1280 x 1024 pixels
	Viewing Angel(H/V)	120°/140°
Main System	Mainboard	SBC86831
	CPU	Socket M for Intel [®] Core™2 Duo/Core™
		Duo/Core™ Solo processor with FSB
		533/667 MHz

Ultra slim design: 84 mm

The PANEL1175-831 has an ultra slim thickness of 84 mm only with streamlined mechanical layout. It not only decreases maintenance time but also saves the space considerably. The PANEL1175-831 is ideal for space-limited environment.

Speaker & WLAN antenna supported

The PANEL1175-831 features built-in speakers for KIOSK application to display multimedia program. It also supports WLAN module (optional) & antenna for wireless network connectivity.

Chipset	Intel [®] 945GME+ICH7M/-DH
System Memory	2 x 240-pin DDR2 DIMM max. up to 4GB
Storage	1 x 3.5" HDD or 2 x 2.5" IDE/SATA HDD
Watchdog Timer	255 levels, 1~255 sec.
Onboard	Intel [®] 945GME integrated
Graphics	



I/O Connector	1 x RS-232/RS-422/RS-485 (COM 1)
	2 x RS-232 (COM 2/3)
	2 x IEEE 1394a
	4 x USB 2.0
	2 x PS/2 keyboard/mouse
	2 x 10/100Mbps Ethernet
	1 x VGA
	1 x Audio (Mic-in/Line-out)
Touchscreen	Resistive type
	Light Transmission 79 %
	Controller RS-232 interface
	Point Activation: 1 million activations (typical)
	at a single point
Power Supply	100 ~ 240VAC, 180W
Dimensions	420mm (16.54") (W) x 84mm (3.31") (D)
	x 354.8mm (13.97") (H)
Weight (net/gross)	9.5 kg (20.9 lb)/15.8 kg (34.8 lb)
Environmental	Operation temperature: 0°C-45°C (32°F-113°F)
	Relative humidity: 10 to 95%@ 40°C, non-condensing
	Operation vibration: 1.0G, 5~500Hz, random
Certification	CE

Ordering Information

	PANEL1175-831	17" TFT Intel [®] Core™2 Duo panel PC with resistive
		touch screen
*Specifications and certifications are limited to optional.		

Optional Accessories

82011750110E	Rack mount bracket kit
82011750070E	VESA & wall mount bracket kit
82011750080E	2 x 2.5" HDD bracket kit
82011750090E	WLAN kit
82011750100E	Desktop stand kit
E202003330	VM-101 (VESA ARM clamp type)
E202003329	VM-105 (VESA ARM wall-mount)

Optional EOS Installation

Windows[®] XP Embedded Windows[®] CE.NET

Optional OS Installation


Windows[®] 2000/XP Windows[®] Vista Home



VESA mounting

Wall mounting

Dimensions



Integrated Solutions for Automation Industry

SCADA

Total Solution for Vertical Markets - VTA Series

> GOT Fanless Touch Panel

PANEL1000 Industrial Panel Computers

PANEL6000 Industrial Flat Panel Monitor

Embedded Field Controller

Industrial Networking

> ata Acquisitior Control Cards